

Liefersortiment / Sommaire de livraison empfohlene Drehzahl/vitesse recommandée

Ø mm	Ø °	Art. Nr. No. Art.	Gewinde Adapter pas-d-vis Adapter		Fr./St. Fr./pce.	Eisen		Guss fonte	Messing		Holz bois
						fer	inox		laiton	alu	
14	9/16	651 090	1/2" x 20G	651 061	16.60	580	300	400	800	900	1600
	5/8	651 100		- 651 069		12.50	550	275	360	750	800
16	-	651 105			12.50	500	250	330	650	750	1600
17	11/16	651 110			12.50	500	250	330	650	750	1600
19	3/4	651 120			12.50	460	230	300	600	700	1500
20	-	651 125			12.50	440	220	290	580	670	1500
21	13/16	651 130			12.50	425	210	280	560	650	1500
22	7/8	651 140			12.50	390	195	260	540	670	1500
24	15/16	651 150			12.50	370	185	245	500	560	1400
25	-	651 155			13.-	350	175	235	470	530	1400
25,4	1	651 160			13.-	350	175	235	470	530	1400
27	1 1/16	651 170			13.-	325	160	215	430	480	1300
29	1 1/8	651 180			13.-	300	150	200	400	450	1300
30	-	651 185			13.-	290	145	195	380	420	1200
30,2	1 3/16	651 190			13.-	285	140	190	380	420	1200
31,7	1 1/4	651 204			13.20	275	135	180	360	410	1200
32	-	651 205			13.20	260	130	170	350	400	1100
35,2	1 3/8	651 224			15.50	250	125	165	330	375	1100
35	-	651 225			15.50	250	125	165	330	375	1000
38	1 1/2	651 244			15.50	230	115	150	300	350	1000
32	1 1/4	651 200	5/8" x	651 069	13.20	275	135	180	360	410	1200
33	1 5/16	651 210	18 G	- 651 077	13.20	260	130	170	340	390	1100
35	1 3/8	651 220			15.50	250	125	165	330	375	1100
37	1 7/16	651 230			15.50	240	120	160	320	360	1100
38	1 1/2	651 240			15.50	230	115	150	300	340	1100
39,7	1 9/16	651 250			15.50	220	110	145	290	330	1100
40	-	651 255			15.50	210	105	140	280	320	1000
41	1 5/8	651 260			15.50	210	105	140	280	320	1000
43	1 11/16	651 270			15.50	205	100	135	270	300	1000
44	1 3/4	651 280			18.30	195	100	130	260	290	1000
45	-	651 285			18.30	195	95	130	260	290	1000
46	1 13/16	651 290			18.30	190	95	125	250	280	1000
48	1 7/8	651 300			18.30	180	90	120	240	270	1000
50	-	651 315			18.30	170	85	115	235	260	900
51	2	651 320			18.30	170	85	115	235	260	900
52	2 1/16	651 330			21.70	165	80	110	220	245	900
54	2 1/8	651 340			21.70	160	80	105	200	230	800
55	-	651 345			21.70	160	80	105	200	230	800
57	2 1/4	651 360			21.70	150	75	100	200	230	800
59	2 5/16	651 370			21.70	145	75	100	195	220	800
60	2 3/8	651 380			21.70	140	70	95	190	215	800
64	2 1/2	651 400			23.20	135	65	90	180	205	800
65	2 9/16	651 410			23.20	130	65	85	175	200	800
67	2 5/8	651 420			23.20	130	65	85	170	195	800
68	-	651 425			23.20	130	65	85	170	195	800
70	2 3/4	651 440			23.20	125	60	80	160	180	800
73	2 7/8	651 460			23.20	125	60	80	160	180	800
75	-	651 475			24.-	120	60	80	160	180	800
76	3	651 480			24.-	115	55	75	150	170	700
79	3 1/8	651 500			24.-	110	55	70	145	165	700
83	3 1/4	651 520			24.-	105	50	70	140	155	700
86	3 3/8	651 540			24.-	100	50	65	130	150	700
89	3 1/2	651 560			24.-	95	45	65	125	145	600
92	3 5/8	651 580			28.-	95	45	60	120	140	600
95	3 3/4	651 600			33.-	90	45	60	120	135	600
98	3 7/8	651 620			35.-	90	45	60	115	125	600
100	-	651 630			36.50	85	40	55	110	120	500
102	4	651 640			36.50	85	40	55	110	120	500
105	4 1/8	651 660			40.-	80	40	50	100	120	500
108	4 1/4	651 680			52.-	80	40	50	100	110	450
111	4 3/8	651 700			61.-	75	35	50	100	110	450
114	4 1/2	651 720			71.50	75	35	50	95	105	450
121	4 3/4	651 760			79.50	65	30	45	90	100	400
127	5	651 800			88.50	60	30	40	80	85	400
140	5 1/2	651 880			105.-	55	25	35	75	80	400
146	5 3/4	651 920			115.-	50	23	30	70	75	400
152	6	651 960			123.-	50	23	30	70	75	400